## IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

## Listing of Claims:

1.(Currently Amended) A down converter (100), comprising: at least one switch;

an interface section, which connects the down converter to the at least one switch; (104), and each switch is connected to a respective

at least one driver circuit (102) is connected to the at least one switch; and

a decoder connected to the at least one switch, wherein the current at least one driver circuits circuit and the switches at least one switch are disposed on a common integrated circuit (200), and wherein the decoder is connected to a signal ground which is different from a power ground of the common integrated circuit.

- 2.(Currently Amended) A—The down converter as recited in claim 1, wherein each of the at least one driver circuit is a high-current driver circuit—(102), and each of the at least switches switch is a power switch—(104).
- 3. (Currently Amended) A—The down converter as recited in claim 1, wherein the interface section is monolithically integrated with the at least one power—switch.
- 4. (Currently Amended) A\_The\_down converter as recited in claim 1, wherein the down converter includes a high-side current driver (102), which is connected to a high-side power switch (104).
- 5. (Currently Amended) A—The down converter as recited in claim 1, wherein the down converter includes a low-side current driver (103), which is connected to a low-side power switch—(105).
- 6.(Currently Amended) A-The down converter as recited in claim 4, wherein the high side current driver is connected to a level shifter (102).

- 7.(Currently Amended) A\_The\_down converter as recited in claim 5, wherein a\_the\_decoder (106)\_is connected to the low side block\_current\_driver\_and to a level shifter.
- 8. (Currently Amended) A—The down converter as recited in claim 4, wherein the high-side current driver is a CMOS device (202, 203).
- 9.(Currently Amended) A The down converter as recited in claim 5, wherein the low-side current driver is a CMOS device—(214, 215).
- 10.(Currently Amended) A\_The down converter as recited in claim 1, wherein a parasitic inductor between a current the at least one driver circuit and a\_the at least one switch is on the order of approximately 1 nH or less.
- 11.(Currently Amended) A The down converter as recited in claim 1, wherein the integrated circuit is a silicon-based

integrated circuit.

12.(Currently Amended) A\_The\_down converter as recited in claim 1, wherein the integrated circuit is a SiGe-based integrated circuit.